






West Region Office:
 WolfVision, Inc.
 1601 Bayshore Highway, Suite 168
 Burlingame, CA 94010
 Tel: (650) 648-0002
 E-mail: sales@wolfvision.us



East Region Office:
 WolfVision, Inc.
 2055 Sugarloaf Circle, Suite 125
 Duluth, GA 30097
 Tel: (770) 931-6802
 E-mail: sales@wolfvision.us

US LIST PRICES JANUARY 1, 2013

Desktop/Portable Visualizer		Availability	MSRP
VZ-3		Now	\$ 2,850.00
VZ-3s		Now	\$ 3,050.00
VZ-8light⁴		Now	\$ 3,790.00
VZ-8plus⁴		Now	\$ 5,650.00
VZ-9plus³		Now	\$ 6,970.00
Feature-Pack for VZ-8light⁴ (optional)	Infrared remote control, memory extension via USB stick, 9 image internal memory, seamless cross-fading between image sources, user defined settings can be stored on USB stick, live to freeze comparison (PiP)	1 st Quarter 2013	\$780.00






Ceiling Visualizer/Stand Alone Cameras		Availability	MSRP
EYE-10		Now	\$ 3,380.00
EYE-12		Now	\$ 4,570.00

West Region Office:
 WolfVision, Inc.
 1601 Bayshore Highway, Suite 168
 Burlingame, CA 94010
 Tel: (650) 648-0002
 E-mail: sales@wolfvision.us



East Region Office:
 WolfVision, Inc.
 2055 Sugarloaf Circle, Suite 125
 Duluth, GA 30097
 Tel: (770) 931-6802
 E-mail: sales@wolfvision.us

Ceiling Visualizer		Availability	MSRP
VZ-C12³		Now	\$ 14,730.00
VZ-C32³		Now	\$ 24,260.00
VZ-C3D		1 st Quarter 2013	\$ 29,980.00

Accessories		Availability	MSRP
Write-On-Surface	Optional dry erase surfaces for any desktop unit (set of 2)	Now	\$ 48.00
EYE-Kit 	EYE-10, EYE-12: Ceiling mount for suspended ceiling or sheetrock.	Now	\$ 230.00
Close-up Lens 	EYE 10, EYE-12: For focal distance lower than 18.8"/1.56' (f=477mm)	Now	\$ 270.00
Tilted Working Plate 	EYE-10, EYE-12: For transparencies.	Now	\$ 230.00
LB-9 	Lightbox: 11.8" x 8.3" (300 x 210mm) for x-rays and slides. Works with all units.	Now	\$ 310.00
LB-38 	Lightbox: 16.9" x 14.1" (430 x 359mm) for x-rays and slides. Works with all units.	Now	\$ 910.00
Supplies	Carry Cases, Bulbs, etc.	www.wolfvision.us	

	Desktop Visualizers						Cameras & Ceiling Visualizers		Ceiling Visualizers		
	VZ-3	VZ-3s	VZ-8light ⁴	VZ-8light ⁴ with Feature-Pack	VZ-8plus ⁴	VZ-9plus ³	EYE-10	EYE-12	VZ-C12 ³	VZ-C32 ³	VZ-C3D
Camera	CCD	CCD	CMOS	CMOS	CMOS	CCD	CCD	CCD	CCD	3-CCD	CMOS
2-Dimensional / 3-Dimensional	2D	2D	2D	2D	2D	2D	2D	2D	2D	2D	3D + 2D
Horizontal resolution (in lines)	710	710	980	980	980	820	640	820	820	1200	980
Frames per second	30	30	30	30	60	30	30	30	30	30	30
Effective megapixels per second	36.8	36.8	62.2	62.2	124.4	36.8	23.6	36.8	36.8	110.6	124.4
Native pixels of camera sensor	1280 x 960	1280 x 960	1920 x 1080	1920 x 1080	1920 x 1080	1280 x 960	1024 x 768	1280 x 960	1280 x 960	1280 x 960	1080p in 3D
Native pixels of image processing	1280 x 960	1280 x 960	1920 x 1080	1920 x 1080	1920 x 1080	1280 x 960	1024 x 768	1280 x 960	1280 x 960	1280 x 960	1080p in 3D
Easy positioning of objects with "Synchronized Light Field"	-	-	-	-	-	-	-	-	●	●	●
Easy positioning of objects with "Synchronized Laser Markers"	-	-	-	-	-	●	-	-	-	-	-
Built-in LCD preview monitor	-	-	-	-	●	●	-	-	-	-	-
Live to Freeze comparison (on two displays or picture-in-picture)	-	-	-	●	●	●	-	-	●	●	-
Firmware upgradable	●	●	●	●	●	●	●	●	●	●	●
Lens type (wide-angle or tele-zoom)	wide	wide	wide	wide	wide	wide	wide	wide	tele	tele	wide
Optical zoom factor	12x	12x	14x	14x	14x	16x	12x	12x	16x	16x	12x
Digital zoom factor	2x	2x	2x	2x	2x	4x	2x	4x	4x	4x	-
High Speed Autofocus + Manual focus	●	●	●	●	●	●	●	●	●	●	●
Manual iris	-	-	-	●	●	●	●	●	●	●	●
Shadow-free illumination / Illumination of hollow objects	-	-	-	-	-	-	-	-	●	●	●
Total tilt range of camera	-	-	220°	220°	220°	290°	-	-	-	-	-
Tilt range of camera to audience / to speaker	-	-	100/120	100/120	100/120	180/110	-	-	-	-	-
Turntable-mounted (with table lock bolt)	-	-	-	-	-	●	-	-	-	-	-
Arm system (mechanical, articulated or pneumatic)	mech.	mech. with 90° swivel plate	pneu.	pneu.	pneu.	artic.	-	-	-	-	-
User-programmable presets	-	-	1	3	3	3	3	3	3	3	3
Special working surface for transparencies	●	●	●	●	●	●	optional	optional	●	●	●
Dry-erase working surface	optional	optional	optional	optional	optional	optional	optional	optional	optional	optional	optional
Computer input / Input switch	●	●	●	●	●	●	-	-	●	●	-
Seamless switch with fading effects	-	-	-	●	●	●	-	-	●	●	-
Image memory (number of pictures)	1	1	1	9 + USB-stick	9 + USB-stick	9 + USB-stick	4	9	9 + USB-stick	9 + USB-stick	-
Digital image output	DVI	DVI	HDMI	HDMI	HDMI	DVI	-	DVI	DVI	DVI	HDMI
Analog image output	VGA	VGA	VGA	VGA	VGA	VGA	VGA	VGA	VGA	VGA	-
USB 2.0 Device port	●	●	●	●	●	●	-	●	●	●	-
USB 2.0 Host port	-	-	-	●	●	●	-	-	●	●	-
RS232 port	-	●	-	-	-	●	●	●	●	●	-
Ethernet (LAN) port	basic	basic	basic	basic	●	●	-	●	●	●	●
LAN features (unicast/multicast streaming)	-	-	-	-	●	●	-	●	●	●	●
Remote Control (with laser pointer)	-	-	-	Infrared	Infrared	Infrared	Infrared	Infrared	Infrared	Infrared	Infrared
Smartphone Remote compatible	●	●	●	●	●	●	-	●	●	●	●
Warranty (in years)	5	5	5	5	5	5	5	5	5	5	5

All units manufactured in European Union (Austria).